

This product is discontinued



Features

- Integrated management of access control and the attendance
- 2.4-inch LCD screen to display the time, the date and swiping/fingerprint authentication results
- Supports registering fingerprints from the terminal to software remotely
- Max. 3000 users, Max. 3000 fingerprints and Max. 100,000 event records
- Two attendance authentication modes: authentication by person, authentication by device
- Stand-alone operation: locally add person, card and fingerprint information
- Exports the swiping card data and the attendance report to the USB
- Up to 32 normal shifts and up to 32 man-hour shifts can be configured
- Up to 32 attendance holiday schedules and up to 128 access control holiday schedules can be configured
- Generates the attendance report automatically and view the attendance data easily
- The doorbell can connect the third party bell
- Tamper alarm and duress alarm function
- It is available to connect the external secure door control unit via RS-485 to avoid the door opening when the terminal is destroyed
- Intelligent English input
- Supports the third party alarm input.

Model No.	VIS-3013S
Operating System	Linux
Storage	Up to 3000 Valid Cards; Up to 100,000 Records, Up to 150,000 Attendance Records
Fingerprint Capacity	Up to 3000 Fingerprints; Up to 10 Fingerprints for Each Person
Fingerprint Comparing Mode	1:1 and 1:N, N=3000
Card Reading Response Duration	< 1 s
Fingerprint Authentication Duration	< 1 s
FAR (False Accept Rate)	≤ 0.001 %
FRR (False Rejection Rate)	≤ 0.01 %
Fingerprint Recognizer	Optical Fingerprint Recognizer Module
External Card Reader	Standard Wiegand26/34



Disclaimer: VISIONIS reserve the right to go ahead with any modifications of models or features or price without forewarning. All the information and specifications stated in this document are current at the time of publication. Attention: We are not responsible for the improper installation of this kit. If you are not handy with electrical equipment you should contact a professional electrician. You will also need to check with your local Fire authority to see if you need anything else to comply with local Fire Codes. We are not responsible for any damage or fees that can occur.



sales@visionistech.com



www.visionistech.com

This product is discontinued

Model No.	VIS-3013S
Card Reading Mode	Supports EM Card, Including Cards with Special Shapes; Supports Reading Card in Metal Environment
Card Reading Distance	0 to 5cm
Keyboard	Keyboard (Back Light)
Reset Key	× 1
Communication Interface	TCP/IP, RS-485 (For Secure Door Control Unit), Wiegand Output (W26/W34) and Input (Wiegand 26/34)
Wi-Fi	Support
Wiegand Interface	Output: Wiegand 26/34; Input: Wiegand 26/34
Transmission Rate	TCP/IP: 10/100Mbps, Self-adaptive; RS485: 19200 bps-N-8-1
Input Interface	Exit Button × 1, Door Sensor × 1 and Alarm Input × 1
Output Interface	Relay (Lock Output) × 1, and Alarm Output × 1
USB	USB 2.0; Type A
LCD Screen	2.4-inch (320 × 240 LCD-TFT Display Screen)
Audio	1 Buzzer and 1 Loudspeaker
LED Indicator	Power/Status (Red/Green)
Power Supply	12 VDC/2 A
Working Temperature	-10 ° C to 55 ° C (14 ° F to 131 ° F)
Working Humidity	10% to 90% (No Condensing)
Waterproof	IP42
Temper-Proof	Support
Appearance Color	Silver
Dimension (L × W × H)	205 mm × 76.5 mm × 37 mm (8.07" × 3.01" × 1.46")
Installation	Surface Mounting, Metal Door Mounting, Installation with Gang Box



Disclaimer: VISIONIS reserve the right to go ahead with any modifications of models or features or price without forewarning. All the information and specifications stated in this document are current at the time of publication. Attention: We are not responsible for the improper installation of this kit. If you are not handy with electrical equipment you should contact a professional electrician. You will also need to check with your local Fire authority to see if you need anything else to comply with local Fire Codes. We are not responsible for any damage or fees that can occur.



sales@visionistech.com



www.visionistech.com