



Features

The VIS-3016 Fingerprint Recorder supports living fingerprint registration, and identification. It can connect to the computer directly via USB interface, and upload/download fingerprint characteristic data and image to the controller/module. It supports the function of checking the completeness of registered fingerprint templates.

- 508 dpi high-definition
- Supports the function of PnP (Plug and play)
- Optical fingerprint sensor designed with scratch-resistant material
- Applies to Windows operation system
- Supports configuration and operation via client software
- USB 2.0 communication standard for data transmission
- Power over USB
- Composite fingerprint images from triple collection

Model No.	VIS-3016
CPU	32bit MCU
Fingerprint Reader	Optical, Red Backlight
FAR	< 0.001 % (Security Level:3)
FRR	< 0.1 % (Security Level:3)
Resolution	508 dpi
Fingerprint Template Size	256*288 (pixel)
Operating Voltage	5 VDC, 200mA
Communication Interface	USB 2.0
Temperature	-30°C to +70°C (-22°F to 158°F)
Humidity	20% to 80%
Operation System	Windows
Dimension (L*W*H)	100mm × 48mm × 35mm (3.93in. x 1.88in. x 1.37in.)



Disclaimer: VISIONIS reserve the right to go ahead with any modifications of models or features or price without forewarning. All the information and specifications stated in this document are current at the time of publication. Attention: We are not responsible for the improper installation of this kit. If you are not handy with electrical equipment you should contact a professional electrician. You will also need to check with your local Fire authority to see if you need anything else to comply with local Fire Codes. We are not responsible for any damage or fees that can occur.



sales@visionistech.com



www.visionistech.com