



**CE RoHS**

The VISIONIS Request-to Exit Buttons and Switches offers a variety of options to fit several applications needs.

The VISIONIS line is designed to provide a reliable source of egress access controlled opening devices in residential, commercial and Industrial locations.

The VISIONIS Request-to Exit Buttons may be connected to the request-to-exit input of any access control device or directly connected to an electromagnetic lock or electric strike Device.

Model No.	VIS-7035
Contact Rating	3A/125-250VAC
Output Contact	NO/NC/COM
Button Installation Diameter	22mm (0.86in.)
Button Color	Green
Panel	1.7mm (0.06in.) Thick 304 Stainless steel
Suitable for	Hollow Door
Mechanical Life	100.000 tests
Operating Temperature	-20°C~+55°C (14°F-131°F)
Operating Humidity	0-95% (relative humidity)
Weight	0.25kg
Dimension Of Plate	115L × 70W × 30H mm - 4.52L x 2.75W x 1.18H in.



**Disclaimer:** VISIONIS reserve the right to go ahead with any modifications of models or features or price without forewarning. All the information and specifications stated in this document are current at the time of publication. Attention: We are not responsible for the improper installation of this product. If you are not handy with electrical equipment you should contact a professional electrician. You will also need to check with your local Fire authority to see if you need anything else to comply with local Fire Codes. We are not responsible for any damage or fees that can occur.



[sales@visionistech.com](mailto:sales@visionistech.com)



[www.visionistech.com](http://www.visionistech.com)