



The VISIONIS Request-to Exit Buttons and Switches offers a variety of options to fit several applications needs.

The VISIONIS line is designed to provide a reliable source of egress access controlled opening devices in residential, commercial and Industrial locations.

The VISIONIS Request-to Exit Buttons may be connected to the request-to-exit input of any access control device or directly connected to an electromagnetic lock or Electric strike Device.

Features

- With Timer Delay Function (1~180 seconds).
- "PUSH TO EXIT" & "PRESIONE PARA SALIR" inserts included.
- Fits into standard single-gang box.
- Large square green color push button.
- 12-Inch, AWG 18 wire leads.
- Illum. S.P.D.T.

Model No.	VIS-7100
Degree of Protection	IP-40
LED	Yes
LED Life	20.000 hours
Switch Material	Plastic
Switch Plate Material	Stainless Steel
Dimension of Mounted Switch	57 mm or 2.24 Inch
Dimension of Exit Button	115L×70W×5H mm or 4.52L×2.75W×0.19H Inch
Background Color	Green Color + PUSH TO EXIT (Black Word)
Standard	U.S.A. Standard
NO/NC contact rate	10A@125~250 VAC
Time Delay	1~180 seconds



Disclaimer: VISIONIS reserve the right to go ahead with any modifications of models or features or price without forewarning. All the information and specifications stated in this document are current at the time of publication. Attention: We are not responsible for the improper installation of this kit. If you are not handy with electrical equipment you should contact a professional electrician. You will also need to check with your local Fire authority to see if you need anything else to comply with local Fire Codes. We are not responsible for any damage or fees that can occur.



sales@visionistech.com



www.visionistech.com