



The Wireless Request to Exit Button has a 433MHz rolling code of encryption algorithm and the split design guarantees higher-secure.

Because of ultra-low power consumption, the exit button can work as long as one year (bases on 20 times/day), with just 1 unit Li-battery.

Features

- 433MHz Communication Frequency
- Easy installation by 3M stickers
- Dry contact version optional (current: 2A)
- 2032 lithium battery operated
- Dimension: L80 x W38 x D15(mm) - L3.15 x W1.50 x D0.59 (in.)

Model No.	VIS-8013
Operating Voltage	1unit of 2032 Lithium battery (INCLUDED)
Idle Current	≤10uA
Working Current	≤30mA
Communication Frequency	433MHz
Communication Distance	50m Maximum (165 feet)
Operating Temperature	-20°C~60°C (-4°F~140°F)
Operating Humidity	0%~86%RH
Dimensions	L80 x W38 x D15(mm) - L3.15 x W1.50 x D0.59(in.)
Unit Weight	34g



Disclaimer: VISIONIS reserve the right to go ahead with any modifications of models or features or price without forewarning. All the information and specifications stated in this document are current at the time of publication. Attention: We are not responsible for the improper installation of this kit. If you are not handy with electrical equipment you should contact a professional electrician. You will also need to check with your local Fire authority to see if you need anything else to comply with local Fire Codes. We are not responsible for any damage or fees that can occur.



sales@visionistech.com



www.visionistech.com