



The VIS-DP102-FSE-LED is an all metal construction electric bolt with 1200kg/2600lbs holding force.

Features

- Holding Strength: 1200Kg (2600lbs)
- Time Delay: 0, 3, 6s
- Function: Fail Secure (with power it's unlock)
- Coil type: pure copper coil, ultra-low temperature continuous work
- Provides reverse current protection
- All metal mechanical structure, safe & durable
- Wide voltage DC12V-DC24V design for all security, building, fire power supply system
- With 10 sec door sensor detection function: the lock won't automatically open if remove the magnet plate after lock 10 sec

Model No.	VIS-DP102-FSE-LED
Voltage	DC12V - DC24V
Holding Force	1200Kg (2600lbs)
Current	(DC12V): Standby 110mA
Function	Fail Secure. N/O with power it's unlock
Time Delay	0/3/6 sec; Unlock time delay: 6 sec (If do not push the door after unlocking, again automatically lock)
Bolt	SUS 304 solid stainless steel
Size	175Lx25Wx35H (mm) - 6.89Lx0.98Wx1.38H (in.)
Product + Packaging Weight	0.64Kg (1.41 pounds)
Operating Temperature	-20°C / +50°C (-4°F / 122°F)
Cycles Tested	300.000



Disclaimer: VISIONIS reserve the right to go ahead with any modifications of models or features or price without forewarning. All the information and specifications stated in this document are current at the time of publication. Attention: We are not responsible for the improper installation of this kit. If you are not handy with electrical equipment you should contact a professional electrician. You will also need to check with your local Fire authority to see if you need anything else to comply with local Fire Codes. We are not responsible for any damage or fees that can occur.



sales@visionistech.com



www.visionistech.com