



2 colors in 1 Exit Sign



Features

- Injection-molded thermoplastic ABS housing, UL 94V-0 flame rating.
- Letters 6" (152.4mm) height with 3/4" stroke.
- Single or double face (Universal).
- Universal J-box mounting pattern.
- 120V/277VAC Dual voltage operation.
- Ultra bright RED or GREEN LEDs., use an internal switch to change the LED light color.
- Built-in 1.2V1000mAh Nickel cadmium battery for minimum 90 minutes emergency operation.
- Maximum 24 hours for full recharge time.
- Test switch and charge indicator.
- UL and CULus listed.
- 0° to 40°C (0° to 104°F) indoor damp location listed.

Model No.	VIS-ESGR
AC Voltage	120/277V / 60Hz
Input Power	0.9W
Output Power	0.36W
AC Charging Current	85mA
Battery	1.2V 1000mAh Ni-MH
Discharge Time	≥ 90mins
Charging Time	24h
Dimensions	295(L) x 182(W) x 46(H)mm - 11.62(L) x 7.17(W) x 1.82(H)in.



Disclaimer: VISIONIS reserve the right to go ahead with any modifications of models or features or price without forewarning. All the information and specifications stated in this document are current at the time of publication. Attention: We are not responsible for the improper installation of this kit. If you are not handy with electrical equipment you should contact a professional electrician. You will also need to check with your local Fire authority to see if you need anything else to comply with local Fire Codes. We are not responsible for any damage or fees that can occur.



sales@visionistech.com



www.visionistech.com