



Wide input range, stable voltage output, overload protection, short-circuit protection, and low output ripple.

All VISIONIS power adapters undergo rigorous full-load and aging tests to ensure maximum durability and reliability.

Designed with an attractive appearance and user-friendly design.

Model No.	VIS-CP200
Input Voltage Range	AC90V-264V
Input Frequency Range	50Hz-60Hz
Output Voltage Range	DC12V+/-5%
Output Current	2A
Output Power	24W
Output Ripple&Noise	≤46MV
Output Efficiency	≥79%
Environment Operating	-30°C~45°C 20%~90%RH
Environment Storage Temp.	-40°C~85°C 10%~95%RH
Product Dimension	87*36.5*70mm (3.42x1.43x2.75in.)
Product Weight	116g
Cable Length	1.2 meters (4 feet)
Certificate	UL, CE, RoHS, FCC



**Disclaimer:** VISIONIS reserve the right to go ahead with any modifications of models or features or price without forewarning. All the information and specifications stated in this document are current at the time of publication. Attention: We are not responsible for the improper installation of this kit. If you are not handy with electrical equipment you should contact a professional electrician. You will also need to check with your local Fire authority to see if you need anything else to comply with local Fire Codes. We are not responsible for any damage or fees that can occur.



support@visionistech.com



www.visionistech.com