



Features

- General Protection: Individual PTC (Positive Temperature Coefficient) Fuse and LED indicator on each output, when problem occurs, only affect the individual output, other outputs still working.
- Short Circuit Protection: When short circuit occurs, Individual PTC Fuse will cut off the circuit and when breakdown removed, PTC fuse will automatically be restoring circuit.
- High voltage protection: When high voltage occurs, the surge protection will be hit through to protect the connected device.
- Over Current protection: When over current occurs, the power supply will automatically switch to self-protection status, when it is removed, then it will return to normal state.

Model No.	VISP-2409-5A
Input Voltage Range	AC110V or 220V
Input Frequency Range	60Hz or 50Hz
Output Voltage Range	AC24V+/-5%
Output Current	5 Amperes
Output Power	120 Watt
Output Channel	9 Channels
Output Fuse Type	PTC
Output Fuse Rating	1.1A
Environment Operating	-30°C~45°C 20%~90%RH
Environment Storage Temp.	-40°C~85°C 10%~95%RH
Product Dimension	482*200*65mm (18.97x7.87x2.55in.)
Product Weight	3.8 kg
Certificate	CE, RoHS, FCC, IEC



Disclaimer: VISIONIS reserve the right to go ahead with any modifications of models or features or price without forewarning. All the information and specifications stated in this document are current at the time of publication. Attention: We are not responsible for the improper installation of this kit. If you are not handy with electrical equipment you should contact a professional electrician. You will also need to check with your local Fire authority to see if you need anything else to comply with local Fire Codes. We are not responsible for any damage or fees that can occur.



sales@visionistech.com



www.visionistech.com